

smart 51 KIOSK CARD PRINTER

Compact and Reliable design

Using the compact SMART-51 printing engine constructed with a metal frame and steel ball bearings, SMART-51 Kiosk card printer is designed to fit into various types of self-service Kiosks.

Scalable Capacity

Optimize your capacity and card selection by selecting from 1 up to 4 detachable input hoppers holding either 300 or 500 cards each.

Options

Single sided or dual sided SMART-51 Kiosk card printer can be equipped with magnetic stripe, contact and contactless encoders. Transparent card (with magnetic stripe) printing is supported as a standard feature.

Convenient integration

Using IDP's exclusive SDK, the SMART-51 Kiosk card printer can be easily integrated into integrators application. Integration includes convenient printer operation status information for easy maintenance.

Up to 4 Selectable Hoppers

300 or 500 cards Refillable Cartridge





Compact and Reliable design

Single or Dual sided card printer



※ SMART-51DK 2 Hopper system with 300 cartridge

High capacity, flexible and reliable card printing module for various Kiosks solutions.



- Up to 212 cards/hour (YMCKO)
- Enhanced FINE™ Imaging Technology
- Top-side Mag. Encoding (*Option)
- Support Transparent Cards
- Support CR79 Type (Factory-installed, *Option)




SMART-51 Printer engine


- Flipper
- Control Panel
 - LCD / LED Buttons, Connectors

- Card Selector

- 300 or 500 cards selectable refillable cartridges



- 1 to 4 Hopper Selectable System
 - Up to 2,000 cards
 - Up to 4 different card types
- Scratch Free
- Residual Q'ty Sensor







※ SMART-51DK 2 Hopper system with 300 cartridge

- Compact and Reliable design
 - Metal Frame, Shaft & Bearings
- Customizable bottom plate (Size, Layout of Control Panel & Adaptors, etc.)

DIMENSIONS

SMART-50DK 1 Hopper & 2 Hopper system



SPECIFICATIONS

Model		SMART-51SK	SMART-51DK
Printing	Print Type	Dye-Sublimation	
	Resolution	300dpi / Edge to Edge	
	Dual Side Printing	X	Yes (Flipper Installed)
Card	Card Feeding	Automatic	
	Card Size & Thickness	ISO CR80 or ISO CR79 (Option-Factory installed) 0.38mm (15mil) ~ 1.0mm (40mil)	
	Card Type	PVC, PET, Composite PVC	
Print Speed	Monochrome	5 sec./card (720 cards/hour)	
	YMCKO	Max. 17 sec./card (212 cards/hour)	
	YMCKOK	-	Max. 22 sec./card (164 cards/hour)
Capacity	Input Hopper	1 to 4 Hopper Selectable System	
	Detachable Cartridge	300 or 500 Cards Selectable refillable cartridges	
System	Display & Control Panel	2 Line LCD / 2 LED Buttons	
	Supported Platforms	Microsoft Windows 7 / 8 / 10	
	Communication	USB, Ethernet (Option)	
	Power Supply	Free Voltage (AC 100/ 220V, 50~60Hz)	
	Temperature/Humidity	15~35℃ / 35~70%	
Encoding Option (Factory-installed)	Magnetic	ISO 7811 (Track I, II, III Read/ Write, HiCo/ LoCo), JIS II	
	Contact	ISO 7816 (ID-1)	
	Contactless	MIFARE, ISO 14443 (Type A/ B), ISO 15693, DESFIRE, iCLASS	

*Print Speed : May change under specific condition.

CONSUMABLES

COLOR RIBBONS

YMCKO	250 Cards/Roll
YMCKOK	200 Cards/Roll
YMCFKO	200 Cards/Roll
HYMCKO	350 Cards/Roll

MONO RIBBONS

KO	650 Cards/Roll
K	1200 Cards/Roll
W	1200 Cards/Roll
B	1200 Cards/Roll
R	1200 Cards/Roll
MG	1200 Cards/Roll
MS	1200 Cards/Roll
SO	1200 Cards/Roll

Specifications and availability may change without notice.

IDP Corp., Ltd.

- OFFICE : #601, 50, Digital-ro 33-gil, Guro-gu, Seoul, Korea, 08377
- TEL : +82-2-6099-3700 • FAX : +82-2-6099-3717
- E-mail : sales@idp-corp.com

IDP Americas, Inc.

- OFFICE : 200 Circuit Drive, North Kingstown, RI 02852
- TEL : +1-401-400-7111 • FAX : +1-401-667-7445
- E-mail : sales.na@idpnorthamerica.com

IDP Middle East

- OFFICE : 13F, Jafza View 18, Downtown Jebel Ali P.O.Box 17588, Dubai - U.A.E.
- TEL : +971-4-889-5900
- E-mail : manupark@idp-corp.com